FLEX-Elektrowerkzeuge GmbH
Bahnhofstrasse 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

Surface finishing sanding

ORE 125-2

Order no. 379.069

Technical attributes	ORE 125-2
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing pad	Ø 125 mm
Sanding media fixing	hook and loop
Dust extraction connection	Ø 27 mm
Weight	1,2 kg

Random-orbit sander with speed control

- Sanding speed to suit the material due to speed control. No more damaged workpieces
- Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- Integrated dust extraction and reliable disposal of the sanding dust using large volume filter bag made of tear-resistant paper. The filter bag is protected by an impact-resistant plastic cassette case
- Possible to connect external dust extraction
- Long service life backing plate made of special tough material
- Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- Especially for working round shapes
- Especially suitable for overhead work

Standard equipment
1 velcro backing pad
1 filter cassette + 1 filter bag